

100 to 200MHz - 2 TX Combiner

| ITEM | SPECIFICATION | | | | |
|--------------------|-----------------------------------|--------------------|--------------------|--------------------|--------------------|
| Model Number | UIY2TC1UA108T118NF | UIY2TC1UA118T137NF | UIY2TC1UA136T174NF | UIY2TC1UA150T170NF | UIY2TC1UA150T200NF |
| Frequency Range | 108 ~ 118MHz | 118 ~ 137MHz | 136 ~ 174MHz | 150 ~ 170MHz | 150 ~ 200MHz |
| Insertion Loss | 4.5dB Max. | 4.5dB Max. | 4.5dB Max. | 4.5dB Max. | 4.5dB Max. |
| Isolation | 75dB Min. | 75dB Min. | 70dB Min. | 75dB Min. | 70dB Min. |
| VSWR | 1.2:1 Max. | 1.2:1 Max. | 1.2:1 Max. | 1.2:1 Max. | 1.2:1 Max. |
| Number of Channels | N Female @2xTX N Female @1xANT | | | | |
| Input Power | TX-ANT 50W/CH | | | | |
| Temperature Range | -30~+75°C | | | | |
| Appearance color | Black | | | | |
| Weight | ~6.5 Kg | | | | |

Mechanical Drawing

