



2 to 4GHz - 3 Way Power Divider/Splitter

Design Features


- ♦ High RF performance, ultra-competitive price.
- ◆ Military, space and commercial applications.
- Custom design available upon request.
- Support one year standard warranty.

RF Characteristics

	Model Number	Freq.Range (GHz)	Insertion Loss Max(dB)	Isolation Min(dB)	VSWR Input Max	VSWR Output Max	Phase Unbalance	Amplitude Unbalance	Power (W)		Connector	Temp.(°C)
									Forward	Reverse	Туре	remp.(c)
	UIY3PD4152A 2T4SF	2.0 ~ 4.0	0.6 (Split 4.8dB)	18	1.3	1.3	±5°	±0.4dB	30	3	SMA-F	-55 ~ +85

- Listed are specific frequency ranges and other ranges are available by custom.
- ² Please provide the below information when inquiring and mark * is required.
 - * 1. The specific frequency ranges.
 - 2. Other special requests (such as Insertion Loss, VSWR, Connector Type, Dimension, etc.)

Mechanical Drawing



Unit: mm/ inch, General part tolerance is ±2% unless otherwise stated.

Ver. 5.1

Web: www.uiy.com

E-mail: sales@uiy.com

No. 8, Lane 1, Xintun East Zone, Longgang District, Shenzhen 518172, China. Tel: +86-755-83748888 +86-755-25999990 Fax: +86-755-25999959