

136 to 520MHz – 4 Way Power Divider/Splitter

Design Features

- ◆ High RF performance, ultra-competitive price.
- ◆ Military, space and commercial applications.
- ◆ Custom design available upon request.
- ◆ Support one year standard warranty.

RF Characteristics

Model Number	Freq.Range (MHz)	Insertion Loss Max(dB)	Isolation Min(dB)	VSWR Input Max	VSWR Output Max	Phase Unbalance	Amplitude Unbalance	Power (W)		Connector Type	Temp.(°C)
								Forward	Reverse		
UIY4PD136136A 136T174NF	136 ~ 174	0.6 (Split 6dB)	18	1.3	1.3	$\leq 3^\circ$	$\leq 0.5\text{dB}$	50	2	N-F	-40 ~ +85
UIY4PD136136A 136T174SF	136 ~ 174	0.6 (Split 6dB)	18	1.3	1.3	$\leq 3^\circ$	$\leq 0.5\text{dB}$	50	2	SMA-F	-40 ~ +85
UIY4PD136136A 136T520NF	136 ~ 520	0.6 (Split 6dB)	18	1.35	1.35	$\leq 3^\circ$	$\leq 0.5\text{dB}$	50	2	N-F	-40 ~ +85
UIY4PD136136A 136T520SF	136 ~ 520	0.6 (Split 6dB)	18	1.35	1.35	$\leq 3^\circ$	$\leq 0.5\text{dB}$	50	2	SMA-F	-40 ~ +85


2 Listed are specific frequency ranges and other ranges are available by custom.

2 Please provide the below information when inquiring and mark * is required.

* 1. The specific frequency ranges.

2. Other special requests (such as Insertion Loss, VSWR, Connector Type, Dimension, etc.)

Mechanical Drawing



Unit: mm/ inch, General part tolerance is $\pm 2\%$ unless otherwise stated.

Ver. 5.1