



500 to 2000MHz - 4 Way Power Divider/Splitter

Design Features


- ◆ High RF performance, ultra-competitive price.
- ◆ Military, space and commercial applications.
- Custom design available upon request.
- Support one year standard warranty.

RF Characteristics

Model Number	Freq.Range (MHz)	Insertion Loss Max(dB)	Isolation Min(dB)	VSWR Max	Phase Unbalance	Amplitude Unbalance	Power (W)			
							Forward	Reverse	Connector Type	Temp.(°C)
UIY4PD8562A500T2000SF	500 ~ 2000	1.0 (Split 6dB)	20	1.25	±3°	\pm 0.3dB	30	3	SMA-F	-55 ~ +85

- ² Listed are specific frequency ranges and other ranges are available by custom.
 - Please provide the below information when inquiring and mark * is required.
 - * 1. The specific frequency ranges.
 - 2. Other special requests (such as Insertion Loss, VSWR, Connector Type, Dimension, etc.)

Mechanical Drawing



Unit: mm/ inch, General part tolerance is ±2% unless otherwise stated.

Ver. 5

Web: www.uiy.com

E-mail: sales@uiy.com

No. 8, Lane 1, Xintun East Zone, Longgang District, Shenzhen 518172, China.

Tel: +86-755-83748888 +86-755-25999990 Fax: +86-755-25999959