

### 350 to 520MHz - 6 RX Receiver Splitter

ITEM	SPECIFICATION			
<b>Model Number</b>	UIY6RS1UB350T370NF	UIY6RS1UB380T400NF	UIY6RS1UB410T430NF	UIY6RS1UB450T470NF
<b>Frequency Range</b>	350 ~ 370MHz	380 ~ 400MHz	410 ~ 430MHz	450 ~ 470MHz
<b>Isolation</b>	25dB Min. @RX-RX			
<b>VSWR</b>	1.2:1 Max. @Port    1.3:1 Max. @ANT			
<b>Number of Channels</b>	N Female @6xRX    N Female @1xANT			
<b>Receiver Multicoupler Amp</b>	Yes			
<b>Maximum Amplifier Gain</b>	ANT-RX(+5~+12dBm)±1dBm 1 2 4 8 Dial Switch Combination, 1db Step Adjustable			
<b>Amplifier NF</b>	1.5dB Max.			
<b>Alarm mode</b>	Amplifier fault alarm			
<b>Standard Voltage Required</b>	DC 12V			
<b>Dimensions</b>	2U (440x298.5x88.8mm)			
<b>Temperature Range</b>	-30~+75°C			
<b>Appearance color</b>	Black			
<b>Weight</b>	~5.5 Kg			

Mechanical Drawing

