

8 to 12GHz – Coaxial Circulator

Design Features

- ◆ Can be dual junction even three for high isolation.
- ◆ High RF performance, ultra-competitive price.
- ◆ Military, space and commercial applications.
- ◆ Custom design available upon request.
- ◆ Guaranteed for one year standard.

RF Characteristics

Model Number	Freq. Range (GHz)	Insertion Loss Max(dB)	Isolation Min(dB)	VSWR Max	Forward Power(W)	Reverse Power(W)	Connector Type	Temp.(°C)
UIYBCC1318A8T12SF	8.0 ~ 12.0	0.5	18	1.3	60	60	SMA-F	-55 ~ +85
UIYBCC1318A8T12SMTSFTSF	8.0 ~ 12.0	0.5	18	1.3	60	60	SMA-M to SMA-F to SMA-F	-55 ~ +85
UIYBCC1318A8T12SFTSMTSF	8.0 ~ 12.0	0.5	18	1.3	60	60	SMA-F to SMA-M to SMA-F	-55 ~ +85

² List are specify frequency range and other ranges available.

² Please enter below information when inquiry and mark * is must.


* 1. The specific frequency range

* 2. Power handling (Forward, Reverse, Peak, etc.)

* 3. Connect type (SMA Male/ Female, N Male/ Female, etc.)

* 4. Other special request if have (Insertion Loss, Isolation, VSWR, Temperature, Dimension, etc.)

Mechanical Drawing



Unit: mm/ inch, General part tolerance is $\pm 2\%$ unless otherwise stated.

Ver. 5.1