2 to 4GHz – 4 Port Dual Junction Coaxial Circulator

Design Features

- Can be dual junction even three for high isolation.
- High RF performance, ultra-competitive price.
- Military, space and commercial applications.
- Custom design available upon request.
- Guaranteed for one year standard.

RF Characteristics

Model Number	Freq. Range (GHz)	Insertion Loss (1-2 & 3-4) Max(dB)	Isolation (2-1 & 4-3) Min(dB)	VSWR Max	Forward Power (W)	Reverse Power (W)	Connector Type	Temp.(°C)
UIYBCC6434A4P2T4SF	2.0 ~ 4.0	1.2	34	1.35	100	100	SMA-F	+10 ~ +70
UIYBCC6434A4P2T4NF	2.0 ~ 4.0	1.2	34	1.35	100	100	N-F	+10 ~ +70

- List are specify frequency range and other ranges available.
- Please enter below information when inquiry and mark * is must.
  - * 1. The specific frequency range
  - * 2. Power handling (Forward, Reverse, Peak, etc.)
  - * 3. Connect type (SMA Male/ Female, N Male/ Female, etc.)
  - 4. Other special request if have (Insertion Loss, Isolation, VSWR, Temperature, Dimension, etc.)

Mechanical Drawing



Unit: mm/ inch, General part tolerance is ±2% unless otherwise stated.

Ver. 5

3/F, No 9, Xiangyin Rd, Longgang District, Shenzhen 518116, China. Web: www.uiy.com

Tel: +86-755-25999990 +86-755-25999909 Fax: +86-755-25999959 E-mail: sales@uiy.com