



8 to 12GHz - Dual Junction Drop in Circulator

Design Features


- ◆ Can be in Dual Junction or Multi-Junction for higher isolation.
- ◆ High RF performance, ultra-competitive price.
- ◆ Military, space and commercial applications.
- Custom design available upon request.
- Support one year standard warranty.

RF Characteristics

Model Number	Freq. Range (GHz)	Insertion Loss (1-2) Max(dB)	Isolation (2-1) Min(dB)	VSWR Max	Forward Power(W)	Reverse Power(W)	Connector Type	Temp.(°C)
UIYBDC2619A8T12	8.0 ~ 12.0	1.0	36	1.3	60	60	TAB	-55 ~ +85

- ² Listed are specific frequency ranges and tailor-made ranges are available.
 - Please provide the information below when inquiring and mark * is required.
 - * 1. The specific frequency ranges
 - * 2. Power handling (Forward, Reverse, Peak, etc.)
 - 3. Other special requests (Insertion Loss, Isolation, VSWR, Temperature, Dimension etc.)

Mechanical Drawing



Unit: mm/ inch, General part tolerance is ±2% unless otherwise stated.

Ver. 5

Web: www.uiy.com

E-mail: sales@uiy.com

No. 8, Lane 1, Xintun East Zone, Longgang District, Shenzhen 518172, China. Tel: +86-755-83748888 +86-755-25999990 Fax: +86-755-25999959