



12950 to 13050MHz - Band Pass Filter

Design Features


- ◆ High RF performance, ultra-competitive price.
- ◆ Military, space and commercial applications.
- Custom design available upon request.
- Support one year standard warranty.


RF Characteristics

Model Number	Pass Band (MHz)	Insertion Loss Max(dB)	VSWR Max	Rejection	Power (W)	Connector Type	Temp.(°C)
UIYBPF11033A12950T13050WR62	12950 ~ 13050	1.5	1.3	60dB @12750MHz 60dB @13250MHz	10	WR62	-40 ~ +85

- 2 Listed are specific frequency ranges and tailor-made ranges are available.
- ² Please provide the below information when inquiring and mark * is required.
 - * 1. The specific pass band frequency range
 - * 2. The specific rejection and frequency
 - 3. Other special requests (such as Insertion Loss, VSWR, Connector Type, Dimension, etc.)

Mechanical Drawing





Unit: mm/ inch, General part tolerance is ±2% unless otherwise stated.

Ver. 5

 No. 8, Lane 1, Xintun East Zone, Longgang District, Shenzhen 518172, China.
 Web: www.uiy.com

 Tel: +86-755-83748888
 +86-755-25999990
 Fax: +86-755-25999999

E-mail: sales@uiy.com

 Tel: +86-755-83748888
 +86-755-25999999