

2545 to 2655MHz – Band Pass Filter

Design Features


- ◆ High RF performance, ultra-competitive price.
- ◆ Custom design available upon request.
- ◆ Military, space and commercial applications.
- ◆ Support one year standard warranty.

RF Characteristics

Model Number	Pass Band (MHz)	Insertion Loss Max(dB)	Ripple in-band Max(dB)	VSWR Max	Rejection	Power (W)	Connector Type	Temp.(°C)
UIYBPF15565A2545T2655SF	2545~2655	1.5	0.8	1.3	60dB @DC~2525MHz 60dB @2675~6000MHz	20	SMA-F	-20 ~ +50
UIYBPF15565A2545T2655NF	2545~2655	1.5	0.8	1.3	60dB @DC~2525MHz 60dB @2675~6000MHz	20	N-F	-20 ~ +50

² Listed are specific frequency ranges and tailor-made ranges are available.
² Please provide the below information when inquiring and mark * is required.
 * 1. The specific pass band frequency range.
 * 2. The specific rejection and frequency.
 3. Other special requests (such as Insertion Loss, VSWR, Connector Type, Dimension, etc.)

Mechanical Drawing



Unit: mm/ inch, General part tolerance is $\pm 2\%$ unless otherwise stated.

Ver. 5