

360 to 380MHz – Band Pass Filter

Design Features


- ◆ High RF performance, ultra-competitive price.
- ◆ Military, space and commercial applications.
- ◆ Custom design available upon request.
- ◆ Support one year standard warranty.

RF Characteristics

Model Number	Pass Band (MHz)	Insertion Loss Max(dB)	Ripple	VSWR Max	Rejection	Power (W)	Connector Type	Temp.(°C)
UIYBPF220115B360T380SF	360 ~ 380	1.0	0.6	1.3	100dB@DC~340MHz 100dB@400~2000MHz 80dB@2000~2500MHz	100	SMA-F	-40 ~ +70
UIYBPF220115B360T380NF	360 ~ 380	1.0	0.6	1.3	100dB@DC~340MHz 100dB@400~2000MHz 80dB@2000~2500MHz	100	N-F	-40 ~ +70

² Listed are specific frequency ranges and tailor-made ranges are available.
² Please provide the below information when inquiring and mark * is required.
 * 1. The specific pass band frequency range
 * 2. The specific rejection and frequency
 * 3. Other special requests (such as Insertion Loss, VSWR, Connector Type, Dimension, etc.)

Mechanical Drawing



Unit: mm/ inch, General part tolerance is $\pm 2\%$ unless otherwise stated.

Ver. 5.1