

462.425MHz – Band Stop Filter

Design Features


- ◆ High RF performance, ultra-competitive price.
- ◆ Military, space and commercial applications.
- ◆ Custom design available upon request.
- ◆ Guaranteed for one year standard.

RF Characteristics

Model Number	Band Reject Frequency (MHz)	Pass Frequency (MHz)	Band Reject Rejection Min(dB)	Return Loss Min(dB)	Insertion Loss Max(dB)	Power (W)	Connector Type	Temp.(°C)
UIYBSF11060A462425NF	462.425	450~456.275MHz 462.8675~467MHz	20	15	1.5	50	N-F	-40 ~ +80
UIYBSF11060A462425SF	462.425	450~456.275MHz 462.8675~467MHz	20	15	1.5	50	SMA-F	-40 ~ +80

- ◇ Listed are specific frequency ranges and other ranges are available.
- ◇ Please provide the below information when inquiring and mark * is required.
 - * 1. The specific pass band frequency range.
 - * 2. The specific rejection and frequency.
 - * 3. Other special requests (such as Insertion Loss, VSWR, Connector Type, Dimension, etc.)

Mechanical Drawing



Unit: mm/ inch, General part tolerance is $\pm 2\%$ unless otherwise stated.

Ver. 5.1