

2W 18GHz – Coaxial Attenuator

Design Features

- ◆ High RF performance, ultra-competitive price.
- ◆ Custom design available upon request.
- ◆ Military, space and commercial applications.
- ◆ Guaranteed for one year standard.

RF Characteristics

| Model Number | Freq. Range | Power | Attenuation Value | Attenuation Tolerance | VSWR Max | Connector Type | Impedance |
|---------------|-------------|-------|-------------------|-----------------------|----------|----------------|-----------|
| UIYCA2AN18A3 | DC-18GHz | 2W | 3 dB | ±0.5 dB | 1.4 | N-M / N-F | 50 Ω |
| UIYCA2AN18A6 | DC-18GHz | 2W | 6 dB | ±0.5 dB | 1.4 | N-M / N-F | 50 Ω |
| UIYCA2AN18A10 | DC-18GHz | 2W | 10 dB | ±0.6 dB | 1.4 | N-M / N-F | 50 Ω |
| UIYCA2AN18A20 | DC-18GHz | 2W | 20 dB | ±0.8 dB | 1.4 | N-M / N-F | 50 Ω |
| UIYCA2AN18A30 | DC-18GHz | 2W | 30 dB | ±0.8 dB | 1.4 | N-M / N-F | 50 Ω |

- ² List are specify frequency range and other ranges available.
² Please enter below information when inquiry and mark * is must.
 * 1. Power handling, Attenuation Value
 2. Connect type (SMA Male/ Female, N Male/ Female, etc.)
 3. Other special request if have (VSWR, Temperature, Dimension, etc.)

Mechanical Drawing

