200 to 3600MHz – Drop in Circulator

Design Features

- Can be dual junction or multiple for high isolation.
- Military, space and commercial applications.
- High RF performance, ultra-competitive price.
- Support one year standard warranty.

RF Characteristics

Model Number	Freq. Range (MHz)	Insertion Loss Max(dB)	Isolation Min(dB)	VSWR Max	Forward Power(W)	Reverse Power(W)	Connector Type	Temp.(°C)
UIYDC2525A210T220	210 ~ 220	0.6	18	1.3	200	200	TAB	-40 ~ +85
UIYDC2525A220T230	220 ~ 230	0.5	18	1.3	200	200	TAB	-40 ~ +85
UIYDC2525A250T270	250 ~ 270	0.5	18	1.3	200	200	TAB	-40 ~ +85
UIYDC2525A300T320	300 ~ 320	0.5	20	1.25	200	200	TAB	-40 ~ +85
UIYDC2525A350T370	350 ~ 370	0.4	20	1.25	200	200	TAB	-40 ~ +85
UIYDC2525A380T460	380 ~ 460	0.5	17	1.35	200	200	TAB	-40 ~ +85
UIYDC2525A400T470	400 ~ 470	0.5	18	1.3	200	200	TAB	-40 ~ +85
UIYDC2525A410T425	410 ~ 425	0.3	25	1.15	200	200	TAB	-40 ~ +85
UIYDC2525A430T470	430 ~ 470	0.4	20	1.25	200	200	TAB	-40 ~ +85
UIYDC2525A450T512	450 ~ 512	0.5	20	1.25	200	200	TAB	-40 ~ +85
UIYDC2525A490T510	490 ~ 510	0.25	25	1.15	200	200	TAB	-40 ~ +85
UIYDC2525A600T700	600 ~ 700	0.3	21	1.2	200	200	TAB	-40 ~ +85
UIYDC2525A700T803	700 ~ 803	0.3	23	1.2	200	200	TAB	-40 ~ +85
UIYDC2525A800T1000	800 ~ 1000	0.4	19	1.25	200	200	TAB	-40 ~ +85
UIYDC2525A860T960	860 ~ 960	0.3	23	1.25	200	200	TAB	-40 ~ +85
UIYDC2525A869T894	869 ~ 894	0.2	25	1.15	200	200	TAB	-40 ~ +85
UIYDC2525A925T960	925 ~ 960	0.2	25	1.15	200	200	TAB	-40 ~ +85
UIYDC2525A950T1250	950 ~ 1250	0.5	18	1.3	200	200	TAB	-40 ~ +85
UIYDC2525A1150T1650	1150 ~ 1650	0.5	15	1.45	200	200	TAB	-40 ~ +85
UIYDC2525A1200T1400	1200 ~ 1400	0.3	23	1.2	200	200	TAB	-40 ~ +85
UIYDC2525A1300T1800	1300 ~ 1800	0.5	16	1.4	200	200	TAB	-40 ~ +85
UIYDC2525A1500T1700	1500 ~ 1700	0.3	23	1.2	200	200	TAB	-40 ~ +85
UIYDC2525A1710T2170	1710 ~ 2170	0.4	20	1.25	200	200	TAB	-40 ~ +85
UIYDC2525A1805T1880	1805 ~ 1880	0.2	25	1.15	200	200	TAB	-40 ~ +85
UIYDC2525A1920T1990	1920 ~ 1990	0.2	25	1.15	200	200	TAB	-40 ~ +85
UIYDC2525A2000T2500	2000 ~ 2500	0.5	20	1.25	200	200	TAB	-40 ~ +85
UIYDC2525A2300T2500	2300 ~ 2500	0.25	25	1.15	200	200	TAB	-40 ~ +85
UIYDC2525A2300T2700	2300 ~ 2700	0.3	23	1.2	200	200	TAB	-40 ~ +85
UIYDC2525A2400T2600	2400 ~ 2600	0.25	25	1.15	200	200	TAB	-40 ~ +85
UIYDC2525A2496T2690	2496 ~ 2690	0.25	25	1.15	200	200	TAB	-40 ~ +85
UIYDC2525A2500T2700	2500 ~ 2700	0.25	25	1.15	200	200	TAB	-40 ~ +85
UIYDC2525A2700T3100	2700 ~ 3100	0.25	23	1.2	200	200	TAB	-40 ~ +85
UIYDC2525A3000T3600	3000 ~ 3600	0.3	20	1.25	200	200	TAB	-40 ~ +85

Mechanical Drawing



Unit: mm/ inch, General part tolerance is ±2% unless otherwise stated.

Ver. 5.3

No. 8, Lane 1, Xintun East Zone, Longgang District, Shenzhen 518172, China. Web: www.uiy.com

Tel: +86-755-83748888 +86-755-25999990 Fax: +86-755-25999959 E-mail: sales@uiy.com