

700 to 3100MHz – Drop in Circulator

Design Features

- ◆ Can be dual junction even three for high isolation.
- ◆ High RF performance, ultra-competitive price.
- ◆ Military, space and commercial applications.
- ◆ Custom design available upon request.
- ◆ Guaranteed for one year standard.

RF Characteristics

Model Number	Freq. Range (MHz)	Insertion Loss Max(dB)	Isolation Min(dB)	VSWR Max	Forward Power(W)	Reverse Power(W)	Connector Type	Temp.(°C)
UIYDC3232A700T900	700 ~ 900	0.5	20	1.25	200	200	TAB	-30 ~ +70
UIYDC3232A800T900	800 ~ 900	0.4	20	1.25	200	200	TAB	-30 ~ +70
UIYDC3232A960T1215	960 ~ 1215	0.4	20	1.25	200	200	TAB	-30 ~ +70
UIYDC3232A1600T2000	1600 ~ 2000	0.6	18	1.3	200	200	TAB	-20 ~ +65
UIYDC3232A1800T2200	1800 ~ 2200	0.5	18	1.3	200	200	TAB	-30 ~ +70
UIYDC3232A2000T2400	2000 ~ 2400	0.5	18	1.3	200	200	TAB	-40 ~ +70
UIYDC3232A2400T2500	2400 ~ 2500	0.2	23	1.15	200	200	TAB	-40 ~ +85

² List are specify frequency range and other ranges available.


² Please enter below information when inquiry and mark * is must.

* 1. The specific frequency ranges

* 2. Power handling (Forward, Reverse, Peak, etc.)

3. Other special request if have (Insertion Loss, Isolation, VSWR, Temperature, Dimension, etc.)

Mechanical Drawing



Unit: mm/ inch, General part tolerance is $\pm 2\%$ unless otherwise stated.

Ver. 5

3/F, Building A5, Shenbao Power Industrial Park, Shenzhen 518116, China.

Web: www.uiy.com

Tel: +86-755-83748888 +86-755-25999990

Fax: +86-755-25999959

E-mail: sales@uiy.com