

4 to 7GHz – Dual Junction Drop in Circulator

Design Features


- ◆ Can be dual junction even three for high isolation.
- ◆ High RF performance, ultra-competitive price.
- ◆ Custom design available upon request.
- ◆ Guaranteed for one year standard.

RF Characteristics

Model Number	Freq. Range (GHz)	Insertion Loss (1-2) Max(dB)	Isolation (2-1) Min(dB)	VSWR Max	Forward Power(W)	Reverse Power(W)	Connector Type	Temp.(°C)
UIYDDC2420A45T5	4.5 ~ 5.0	0.8	40	1.25	60	60	TAB	-40 ~ +85
UIYDDC2420A47T52	4.7 ~ 5.2	0.8	40	1.25	60	60	TAB	-40 ~ +85
UIYDDC2420A5T58	5.0 ~ 5.8	0.8	40	1.25	60	60	TAB	-40 ~ +85
UIYDDC2420A5T6	5.0 ~ 6.0	1.0	36	1.3	60	60	TAB	-40 ~ +85
UIYDDC2420A52T59	5.2 ~ 5.9	0.8	40	1.2	60	60	TAB	-40 ~ +85
UIYDDC2420A54T59	5.4 ~ 5.9	0.8	45	1.2	60	60	TAB	-40 ~ +85
UIYDDC2420A55T6	5.6 ~ 6.0	0.6	45	1.2	60	60	TAB	-40 ~ +85
UIYDDC2420A57T59	5.7 ~ 5.9	0.6	45	1.2	60	60	TAB	-40 ~ +85
UIYDDC2420A57T65	5.7 ~ 6.5	1.0	40	1.25	60	60	TAB	-40 ~ +85
UIYDDC2420A6T7	6.0 ~ 7.0	0.7	45	1.2	60	60	TAB	-40 ~ +85
UIYDDC2420A635T655	6.35 ~ 6.55	0.6	45	1.2	60	60	TAB	-40 ~ +85

- 2 List are specify frequency range and other ranges available.
 2 Please enter below information when inquiry and mark * is must.
 * 1. The specific frequency range
 * 2. Power handling (Forward, Reverse, Peak, etc.)
 3. Other special request if have (Insertion Loss, Isolation, VSWR, Temperature, Dimension, etc.)

Mechanical Drawing



Unit: mm/ inch, General part tolerance is ±2% unless otherwise stated.

Ver. 5