

380 to 425MHz – Duplexer / Diplexer

Design Features

- ◆ High RF performance, ultra-competitive price.
- ◆ Custom design available upon request.
- ◆ Military, space and commercial applications.
- ◆ Support one year standard warranty.

RF Characteristics

Model Number	Freq. Range (MHz)		Insertion Loss Max(dB)	Isolation Min(dB)	VSWR Max	Power(W)	Connector Type	Temp.(°C)
UIYDX136179A380T395SF	TX	380 ~ 385	2.5	50	1.5	100	SMA-F	-40 ~ +70
	RX	390 ~ 395						
UIYDX136179A380T395NF	TX	380 ~ 385	2.5	50	1.5	100	N-F	-40 ~ +70
	RX	390 ~ 395						
UIYDX136179A380T429SF	TX	380 ~ 395	2.0	65	1.4	100	SMA-F	-40 ~ +70
	RX	417 ~ 429						
UIYDX136179A380T429NF	TX	380 ~ 395	2.0	65	1.4	100	N-F	-40 ~ +70
	RX	417 ~ 429						

² Listed are specific frequency ranges and tailor-made ranges are available.


² Please provide the information below when inquiring and mark * is must.

* 1. The specific frequency range TX and RX

* 2. Insertion Loss, Isolation, VSWR

* 3. Other special requests (Power handling, Temperature, Dimension, etc.)

Mechanical Drawing



Unit: mm/ inch, General part tolerance is ±2% unless otherwise stated.

Ver. 5