

# 350-470MHz - 2 way Combiner / Hybrid Coupler

## Design Features


- ◆ High RF performance, ultra-competitive price.
- ◆ Military, space and commercial applications.
- ◆ Custom design available upon request.
- ◆ Guaranteed for one year standard.

## RF Characteristics

Model Number	Freq.Range (MHz)	Insertion Loss Max(dB)	Isolation Min(dB)	VSWR Max	Connector Type	Power (W)	Temp.(°C)
UIYHC14844A350T370NF	350 ~ 370	0.5 (Coupling 3dB)	23	1.25	N-F	200(2x100)	-40 ~ +85
UIYHC14844A350T370SF	350 ~ 370	0.5 (Coupling 3dB)	23	1.25	SMA-F	100(2x50)	-40 ~ +85
UIYHC14844A400T470NF	400 ~ 470	0.5 (Coupling 3dB)	25	1.25	N-F	200(2x100)	-40 ~ +85
UIYHC14844A400T470SF	400 ~ 470	0.5 (Coupling 3dB)	25	1.25	SMA-F	100(2x50)	-40 ~ +85

- ◇ Listed are specific frequency ranges and other ranges are available.
- ◇ Please provide the below information when inquiring and mark \* is required.
  - \* 1. The specific frequency range
  - \* 2. Other special requests (such as Insertion Loss, VSWR, Connector Type, Dimension, etc.)

## Mechanical Drawing



Unit: mm/ inch, General part tolerance is  $\pm 2\%$  unless otherwise stated.

Ver. 5