

DC-1500MHz – Low Pass Filter

Design Features


- ◆ High RF performance, ultra-competitive price.
- ◆ Military, space and commercial applications.
- ◆ Custom design available upon request.
- ◆ Support one year standard warranty.

RF Characteristics

Model Number	Pass Band (MHz)	Insertion Loss Max(dB)	VSWR Max	Rejection	Power (W)	Connector Type	Temp.(°C)
UIYLPF18026A490NF	DC-490	0.5	1.3	45dB @850MHz	100	N-F	-40 ~ +85
UIYLPF18026A490SF	DC-490	0.5	1.3	45dB @850MHz	100	SMA-F	-40 ~ +85
UIYLPF18026A500NF	DC-500	1.5	1.5	40dB @700 ~ 2000MHz	50	N-F	-20 ~ +55
UIYLPF18026A1500NF	DC-1500	1.5	1.5	40dB @1700 ~ 3000MHz	50	N-F	-20 ~ +55

² Listed are specific frequency ranges and tailor-made ranges are available.
² Please provide the below information when inquiring and mark * is required.
 * 1. The specific pass band frequency range
 * 2. The specific rejection and frequency
 3. Other special requests (such as Insertion Loss, VSWR, Connector Type, Dimension, etc.)

Mechanical Drawing



Unit: mm/ inch, General part tolerance is $\pm 2\%$ unless otherwise stated.

Ver. 5